Cine-MR Image Segmentation for Assessment of Small Bowel Motility Function Using 3D U-Net

Kazuki Otsuki, Yutaro Iwamoto, and Yen-Wei Chen Graduate School of Information Science and Engineering, Shiga, Japan Email: is0158er@ed.ritsumei.ac.jp, yiwamoto@fc.ritsumei.ac.jp, chen@is.ritsumei.ac.jp

> Akira Furukawa Tokyo Metropolitan University, Tokyo, Japan Email: akira@belle.shiga-med.ac.jp

Shuzo Kanasaki Koseikai Takeda Hospital, Kyoto, Japan Email: shuzo65@hotmail.com

Abstract—In this study, we propose an automated method for assessing small bowel motility function with cine MRI using 3D U-Net, which is a kind of deep fully convolutional neural networks for 3D semantic segmentation. In the proposed method, the cine MR images (temporal MR image sequence) is treated as a 3D image. We applied 3D U-Net, which employs 3D convolution, to automatically segment the temporal small bowel image sequence. Compared with the conventional 2D U-Net, in which the small bowel was segmented without temporal information and just segmented frame by frame, the proposed 3D U-Net can accurately and simultaneously segment all frames using temporal information. This is the first 3D fully convolutional network for small bowel segmentation in cine MR images (temporal sequence images), to the best of our knowledge. The small bowel motility function is assessed by the use of the segmented temporal MR image sequence. Experimental results demonstrate the effectiveness of the proposed method.

Index Terms—cine-MR image, fully convolutional neural network, U-Net, 3D, small bowel, motility

I. INTRODUCTION

The small bowel is responsible for digestion and absorption activities that are essential to human life activity. Therefore, the measurement of this contraction movement is important for the treatment or inspection of the small intestine [1]. Recently, invasive testing method using some endoscope is a common method [2]. However, in this measurement method, the mental and physical burdens of patients are large. The workload of doctor is also very large. For this reason, it was needed to develop an assessment method of the small bowel contraction movement, which has the smallest burdens. In our previous study, we proposed an MR image-based assessment method based on cine MR imaging techniques [3], [4]. Cine MR images [5]-[7] are temporal sequence images that can show small bowel contraction movement. Fig. 1 shows an example of cine-MR images (four frames), where white squares show the targeted small bowel. We measured temporal changes of the small bowel radius, which show the movement of the small bowel. Then we assessed the small bowel contraction movement based on frequency analysis. The limitation of our previous study is that the measurement and analysis were done manually and takes an enormous amount of time and efforts. We also proposed several automatic assessment methods based on image processing techniques [8]-[13]. They can be divided into three groups: (1) segmentation methods [8], [9]; (2) tracking methods [10], [11]; (3) temporal correlation or temporal difference methods [12], [13]. Since the segmentationbased method is more intuitive and contains more information about the small bowel, we focus our research on the segmentation-based method in this paper.

In recent years, deep convolutional neural networks have outperformed state-of-the-art methods in many computer vision tasks, including image classification, image segmentation, and image detection. Particularly, fully convolutional networks (FCNs) [14], [15] have been proposed for semantic segmentation and have achieved impressive performance. U-Net [15] is another deep learning-based semantic segmentation method, which is based on an encoder-decorder architecture. U-Net has been applied in many research fields including medical image segmentation [16]. Since the medical images (such as the CT image) are volume images, 3D U-Net [17] was introduced for medical volume image segmentation, in which 3D convolution as well as 3D pooling operations are employed. Cine MR images are 2D images in spatial space, but they are temporal sequence images (temporal 2D images). Though we can use conventional 2D U-Net to segment the small bowel frame-by-frame, it is timeconsuming and lacks temporal smoothness among frames.

In this paper, we treat the cine-MR image as a 3D image and use a 3D U-Net to segment the small bowel

Manuscript received July 1, 2019; revised November 7, 2019.

from the cine-MR images. Compared with the conventional 2D U-Net, in which the small bowel was segmented frame by frame and no temporal information used, the proposed 3D U-Net can segment all frames simultaneously and accurately by using temporal information. To the best of our knowledge, this is the first

3D fully convolutional network for small bowel segmentation in cine-MR images (temporal sequence images). The small bowel motility function is assessed by the use of the segmented temporal MR image sequence. Experimental results demonstrated the effectiveness of the proposed method.



Figure 1. An example of cine MRI time sequence images. Two small bowels in the left-up and right-down areas are selected manually as the region of interest (ROI) for the analysis, which are indicated using white squares. It is evident that the shape of small bowel changes in time series. Temporal ordering is from left to right.

The remainder of this paper is organized as follows: related works have been summarized in Section II, Section III gives a detailed description of the proposed method, experimental results have been presented and discussed in Section IV, and Section V presents the conclusion.

II. RELATED WORKS

In our previous study, we proposed an optical flow method based on the automatic feature points tracking method [10]. This method comprises of two steps. In the first step, users select two arbitrary points on the boundary of the small bowel in the initial frame. The distance between the two points represents the size of small bowel. In the second step, each of the two points are automatically tracked by the use of Kanade-Lucas-Tomasi (KLT) feature points tracking method [18], [19] in the temporal sequence images. The KLT feature tracker is commonly used for feature point tracking in dynamic images (temporal sequence images). The KLT uses spatial information to search the most appropriate position of the tracking point in the next frame. Examples of automatic feature point tracking results are shown in Fig. 2.



Figure 2. Automatic feature point tracking results. Users arbitrarily specify the red dots in the initial frame. Temporal ordering is from left to right (t=1 to t=70).

Though the tracking method is faster than conventional techniques, there is a problem that the tracking results depend on the initial points setting and it is a semiautomatic method.

III. MATERIALS AND METHOD

A. Dataset

The data used in this research are cine MRI DICOM images (256pixel \times 256pixel \times 70 frames) of four healthy male participants, as shown in Table I. Cine-MR DICOM image is a medical image obtained by consecutively imaging an arbitrary cross-sectional area over a period of time to capture the continuous display of the organ contraction motion in time-sequence (similar to a video image). First, the participant is first in a prone state, and an MR image of the entire abdomen with respect to the coronal plane is captured. Next, concerning the obtained abdomen MR image of the coronal surface, the plane in which the entire area of the small intestine best appears is regarded as the noted section. Finally, by sequentially imaging the section of interest within an arbitrary time, the cine MR temporal sequence images showing the entire small intestine are captured. We performed the cine MRI 10, 15, 30, 45 and 60 min after oral administration of 1500 ml of non-absorbable fluid. When performing the MRI, we obtained 70 frames of cine MRI in 30 s with suspended breath. Fig. 1 shows a typical cine MR image.

In this research, we only focused on a small bowel, which is called the Region of Interest (ROI). An expert manually labels the ROIs. For each cine MR image, we labeled two ROIs in the left-up and right-down areas (which are indicated by white squares in Fig. 1), respectively, for analysis. Each temporal sequence contains 70 frames. The ROI size in each frame is 16×16 pixels. As shown in Table I, we have 32 ROI temporal sequence images in all.

TABLE I. DATA USED IN THIS RESEARCH

Patient No.	Sex	Area	Elapsed time[min]
103	Male	LU, RD	10,15,30,45,60
104	Male	LU, RD	10,15,30,45,60
105	Male	LU, RD	15,30,45
106	Male	LU, RD	15,30,45

B. Network Architecture

In this paper, we proposed an analysis method based on a 3D U-Net [17]. The 3D U-Net usually propagate three- dimensional images as inputs and outputs. Also, we leveraged an image sequence (2D image + time sequence) as inputs and outputs. This modification enables 3D U-Net to maintain and propagate time sequence information along the 3D structure. Fig. 3 illustrates the 3D U-Net network architecture. Like a conventional 2D U-Net, the 3D U-Net has contracting and expanding path. In the contracting path, each layer contains two $3 \times 3 \times 3$ convolutions each followed by a leaky rectified linear unit (Leaky ReLU), and then a $2 \times 2 \times 2$ max pooling with two strides in each dimension. In the expanding path, each layer has an up convolution of $2 \times 2 \times 2$ by strides of two in each dimension, then two $3\times3\times3$ convolutions each followed by a ReLU. Shortcut connections from layers of same tensor shape in the contracting path provide the essential high-resolution features to the expanding path. In the last layer, a $1 \times 1 \times 1$ convolution reduces the number of output channels to the number of labels; we set output channels as 1. The input to the network is a 3D data which consists of $16 \times 16 \times 8$ in x, y, and t directions, respectively. The output in the last layers is also 3D data of $16 \times 16 \times 8$. We also introduce a batch normalization (BN) before each ReLU, and dropout to avoid overfitting.



Figure 3. (a) is the architecture of U-Net and (b) is the architecture of 3D U-Net. Red boxes represent the convolutional and max pooling operations, respectively. Light Green boxes represent batch normalization. Blue boxes represent dropout Layer.

IV. EXPERIMENTAL RESULTS

A. Training and Testing

Training 3D U-Net from scratch requires a large amount of labeled training data. In order to increase the number of training data, each ROI temporal sequence image is divided into 63 sub-temporal sequence images as 3D input images. Each sub-temporal sequence contains eight frames. The frame numbers for each sub-sequence are 1–8, 2–9, 3–10, ..., 63–70. As we described in Sec.3, there are 32 ROI temporal sequences; hence, we have 2016 3D data for training and testing of the proposed 3D U-Net. The size of the 3D data is $16 \times 16 \times 8$. (63 3D ROI images).

We divided our data into four groups with each containing a patient. Table II shows the data distribution. We carried out experiments with 4-fold cross-validation. Three groups were used as training, and one group was used for testing.

The whole network (3D U-Net) is trained end-to-end. Moreover, we ran 300 training epochs on an Nvidia Titan X GPU, which took approximately a day for each phase. We set the learning rate as 10^{-3} for ADAM optimizer and the batch size to 32. The network output and ground truth labels are compared using a sigmoid function with weighted cross entropy loss. Furthermore, the outputs of overlapping areas were combined using majority voting.

TABLE II. DATA DISTRIBUTION

Group No.	Patient No.	Number of 3D data
1	103	630
2	104	630
3	105	378
4	106	378

B. Evaluation Metrics

We used two evaluation metrics, normalized correlation and the Dice coefficient for quantitative evaluations. We used the normalized correlation value of the time-series waveform of the small intestinal contraction movement (temporal areas of the small bowel) between the ground truth x (manually segmented results) and the automatically segmented results y. Equation (1) expresses the normalized correlation, where x_i and y_i are manually and automatically segmented results (areas of segmented small bowel) of the *i*-th frame, respectively. Moreover, \bar{x} and \bar{y} are means of x and y, respectively. The normalized correlation value is close to 1.0, indicating that the segmentation result is similar to the ground truth.

$$Correl(\mathbf{x}, \mathbf{y}) = \frac{\sum (x_i - \bar{x})(y_i - \bar{y})}{\sqrt{(x_i - \bar{x})^2(y_i - \bar{y})^2}}$$
(1)

The Dice coefficient is used as a measure of segmentation accuracy for each frame, which is defined by Eq. (2), where *x* and *y* are manually and automatically segmentation results (binary masks) for each frame, respectively.

$$DSC(x, y) = \frac{2|x \cap y|}{|x| + |y|}$$
(2)

Also, using Fourier transform analysis we examined the frequency of small bowel contraction movement. Eq. (3) represents the Fourier transform, where f(t) is the waveform (temporal change of the segmented small bowel area), F(u) is its spectrum, u is the frequency, and N is the number of temporal frames.

$$F(u) = \sum_{x=0}^{N-1} f(t)e^{-i\frac{2\pi tu}{N}}$$
(3)

C. Results

Fig. 4 shows typical segmentation results using the proposed 3D U-Net. For comparing the method proposed in this paper and the conventional 2D U-Net, we have presented the segmentation results obtained using conventional 2D U-Net in Fig. 4. Also, Fig. 4 shows

results of the manual segmentation by experts, while their waveforms are shown in Fig. 5. Their Fourier transform results are shown in Fig. 6. As shown Fig. 4-Fig. 6, it is evident that the 3D U-Net achieved more accurate segmentation than the other method. Table III summarized the results. For all cine MR images, the proposed 3D U-Net achieved better results as compared to the conventional U-Net. The effectiveness of proposed method has been confirmed experimentally.



Figure 4. Visuallization results of our test set.

		Normalize	ed correlation	Frequer	ncy error	Dice co	efficient
No.	Time	U-Net	3D U-Net	U-Net	3D U-Net	U-Net	3D U-Net
	10	0.79	<u>0.81</u>	0	0	0.82	0.87
	15	0.75	<u>0.81</u>	0	0	0.80	0.82
103	30	0.72	0.72	0	0.033	0.87	<u>0.88</u>
	45	0.62	<u>0.67</u>	0	0	0.81	0.82
	60	0.63	<u>0.70</u>	0.067	0.033	0.79	<u>0.80</u>
	10	0.46	0.62	0.067	0	0.64	<u>0.74</u>
	15	0.60	<u>0.64</u>	0	0	0.72	<u>0.79</u>
104	30	0.82	<u>0.87</u>	0	0	0.75	<u>0.79</u>
	45	0.66	0.76	0.033	0.033	0.81	0.82
	60	0.78	<u>0.84</u>	0	0	0.83	0.85
	15	<u>0.76</u>	0.73	0	0.033	0.81	0.82
	30	0.65	<u>0.98</u>	0.067	0	0.81	0.82
105	45	0.87	<u>0.91</u>	0	0	0.86	<u>0.87</u>
	60	0.54	<u>0.67</u>	0.1	0	0.90	<u>0.93</u>
	15	0.66	0.67	0	0	0.54	0.59
	30	0.48	<u>0.50</u>	0.067	0	0.62	0.58
106	45	0.43	0.48	0.067	0	0.70	<u>0.71</u>
	60	<u>0.36</u>	0.31	0	0.1	0.58	<u>0.61</u>
Mea	n±std.	0.64±0.14	<u>0.70±0.15</u>	0.022±0.033	0.012±0.025	0.76±0.10	0.78±0.10

|--|



Figure 5. Time-series waveforms.



Figure 6. Comparison results of frequency analysis results.

V. CONCLUSION

In this paper, we proposed an automatic analysis method of small bowel motility function using 3D U-Net. For all cine-MR images used in our experiments, the proposed 3D U-Net achieved better results than conventional 2D U-Net. In the future, we are going to assess disease cases and compare them with the healthy cases.

ACKNOWLEDGMENT

This work was supported in part by the Grant-in Aid for Scientific Research from the Japanese Ministry for Education, Science, Culture and Sports (MEXT) under the Grant No. 2546183, and No. 18H03267.

REFERENCES

- H. Husebye., "The patterns of small bowel motility: Physiology and implications in organic disease and functional disorders," *Neurogastroenterol Motil*, vol. 11, pp. 141-146, 1993.
- [2] M. Pennazio, "Small bowel endoscopy," *Endoscopy*, vol. 36, pp. 32-41, 2004.
- [3] M. Wakamiya, A. Furukawa, S. Kanasaki, and K. Murata, "Assessment of small bowel motiilty function with cine-MRI using balanced steady-state free precession sequence," *Journal of Magnetic Resonance Imaging*, vol. 33, pp. 1235-1240, 2004.
- [4] A. Furukawa, S. Kanasaki, M. Wakamiya, K. Murata, X. Wu, T. Tateyama, and Y. W. Chen, "Cross-sectional imaging of the small bowel," in Proc. 6th International Conference on Computer Sciences and Convergence Information Technology, Jeju Island, Korea, 2011, pp. 934-9384.
- [5] P. Asbach, *et al.*, "Cine magnetic resonance imaging of the small bowel: Comparison of different oral contrast media," *Acta. Radiol.*, vol. 47, pp. 899-906, 2006.

- [6] A. Furukawa, et al., "MR imaging in gastrointestinal tracts: Static and dynamic assessment," in Proc. 6th International Conference on New Trends in Information Science, Service Science and Data Mining, Taiwan, pp. 441-445.
- [7] J. M. Froehlich, M. A. Patak, C. V. Waymarm, C. F. Juli, C. L. Zollikofer, and K. U. Wentz, "Small bowel motility assessment with magnetic resonance imaging," *Journal of Magnetic Resonance Imaging*, vol. 21, pp. 370-375, 2005.
- [8] X. Wu, et al., "A semi-automated detection for motility of small bowel with MRI sequence," *IEICE Technical Report*, vol. 109, no. 63, pp. 101-105, 2009.
- [9] D. H. L. Nguyen, et al., "Computerized assessment of small bowel motility function using cine-MR Imaging: Preliminary results in super-pixel segmental method," *Journal of Transportation Medicine*, vol. 71, pp. 88-96, 2017.
- [10] K. Otsuki, A. Furukawa, S. Kanasaki, Y. Iwamoto, T. Tateyama, and Y. W. Chen, "Automated assessment of small bowel motility function based on feature point tracking," in *Proc. 14th International Conference on Natural Computation, Fuzzy Systems* and Knowledge Discovery, Huangshan, China, 2018.
- [11] X. Wu, Q. Xi, Y. W. Chen, and S. Zhang, "Orientation adaptive fast marching method for the countour tracking of small intestine," *Electoronics Letters*, vol. 45, pp. 1154-1155, 2009.
- [12] A. Taniguchi, A. Furukawa, S Kanasaki, T. Tateyama, Y. W. Chen, "Automated assessment of small bowel motility function based on three-dimensional zero-mean normalized cross correlation," in *Proc. 6th International Conference on Biomedical Engineering and Informatics*, Hangzhou, China, 2013, pp. 802-805.
- [13] A. Taniguchi, "Automated assessment of small bowel motility function based on image processing techniques," master thesis, Ritsumeikan University, 2014.
- [14] J. Long and E. Shelhamer, "Fully convolutional models for semantic segmentation," in *Proc. of CVPR*, 2015.
- [15] O. Ronneberger, P. Fischer, and T. Brox, "U-Net: Convolutional networks for biomedical image segmentation," in *Proc. MICCAI*, 2015, pp. 234-241.
- [16] Y. Enokiya, et al., "Automatic liver segmentation using U-net with wasserstein GANs," *Journal of Images and Graphics*, vol. 6, pp. 152-159, 2018.
- [17] O. Cicek, A. Abdulkadir, S. S. Lienkamp, T. Brox, and O. Ronneberger, "3D U-net: Learning dense volumetric segmentation from sparse annotation," in *Proc. MICCAI*, 2016, pp. 424-432.
- [18] C. Tomasi and T. Kanade, "Detection and tracking of point features," technical report CMU-CS-91-132, Carnegie Mellon University, 1991.
- [19] T. H. Ngo, Y. W. Chen, N. Matsushiro, and M. Seo, "Quantitative assessment of facial paralysis based on spatiotemporal features," *IEICE Trans. on Information and Systems*, vol. E99-D, no. 1, pp. 187-196, 2016.



Kazuki Otsuki received the B.E. degree from Ritsumeikan University, Kusatsu, Japan in 2016. He entered the Graduate School of Information Science and engineering, Ritsumeikan University, Kusatsu, Japan, in 2018. His current research interests include medical image analysis and deep learning.



Yutaro Iwamoto received the B.E. and M.E., and D.E. degree from Ritsumeikan University, Kusatsu, Japan in 2011 and 2013, and 2017, respectively. He is currently an Assistant Professor at Ritsumeikan Univiersity, Kusatsu, Japan. His current research interests include image restoration, segmentation, classification of medical imaging and deep learning.



Akira Furukawa is currently a Chair and Professor of Department of Radiological Sciences of Tokyo Metropolitan University (TMU) and of Graduate school of TMU. He has received his M.H. degree in 1984 and PhD degree in Medicine in 1996 form Shiga University of Medical Science, Shiga Japan. He was a resident (1984 - 1986), assistant professor (1986 - 2000), associate professor (2000 - 2007) and senior associate professor

(2007 - 2011) at Department of Radiology in Shiga University of Medical science (SUMS) before he became a professor at TMU. He was also a Research fellow at Radiology Department of Long Island Jewish Medical Center, New York, USA (1995 - 1997) during he was an assistant professor at SUMS.

Akira Furukawa has published many research papers and has received distinguished awards from all over the world. He is the investigator of several projects in the fields of Radiology and Bio-medical Engineering and Image Analysis, funded by Japanese Government.



Shuzo Kanasaki (MD and PhD) graduated from Shiga University of Medical Science, Faculty of Medicine in 1991, obtaining a medical license. He received his PhD from Shiga University of Medical Science, Shiga, Japan, in 2000. He belonged to the Department of Radiology at Shiga University of Medical Science from 1991 to 1996. He entered the Graduate School of Shiga University of Medical Science in 1996 and graduated in 2000. From Apr. 2000 to Mar. 2007, he was a Head Physician and Deputy Director in the department of radiology, Koseikai Takeda Hospital, Kyoto, Japan. From Apr. 2007 to Mar. 2011, he was an assistant professor in the department of radiology, Shiga University of Medical Science. He has been appointed Director of radiology at Koseikai Takeda Hospital in 2011, and has been to date. He acquired a certification of a board certified diagnostic radiology in 1997. His subspecialties are abdominal radiology, emergency radiology and interventional radiology.



Yen-Wei Chen received his B.E. degree in 1985 from Kobe Univ., Kobe, Japan. He received his M.E. degree in 1987, and his D.E. degree in 1990, both from Osaka Univ., Osaka, Japan. He was a research fellow at the Institute of Laser Technology, Osaka, from 1991 to 1994. From Oct. 1994 to Mar. 2004, he was an associate Professor and a professor in the department of Electrical and Electronic Engineering, Univ. of the Ryukus, Okinawa,

Japan. He is currently a professor at the college of Information Science and Engineering, Ritsumeikan University, Japan. He is also a visiting professor at the college of Computer Science and Technology, Zhejiang University, and Zhejiang Lab, Hangzhou, China. His research interests include medical image analysis, pattern recognition.

Yen-Wei Chen has published more than 300 research papers. He has received many distinguished awards. He is the Principal Investigator of several projects in bio-medical engineering and image analysis, funded by Japanese Government.